



MICAPS ECO4KUHD8MPCD

C-mount USB3.0 CMOS Cameras
SONY STARVIS 2 CMOS Sensor



The ECO4KUHD8MPCD camera is a cutting-edge live-view imaging system that boasts 4K resolution video at 30 frames per second. It features a Sony Exmor CMOS sensor known for its high sensitivity and low dark current, ensuring crisp images without smearing thanks to its R, G, and B primary color mosaic filters. This camera is designed with a standard C-mount interface, ensuring compatibility with a wide range of microscopy systems. It can function as a standalone recorder when connected to an HDMI monitor or TV, or it can be live-streamed to a PC via USB for image capture and video recording. The camera includes hardware 3D denoising, sharpness, and tone mapping control functions.

The accompanying Windows software provides tools for image development, measurement, and advanced features like image stitching and extended depth of focus. It can calibrate scales at various magnifications, making it suitable for multi-level inspection tasks. For Mac and Linux users, there's a lite version of the software available, offering video and image capture capabilities with limited processing features. Overall, the ECO4KUHD8MPCD 4K series camera is tailored for acquiring digital images from stereo microscopes, biological microscopes, or for online interactive teaching purposes.

Features

- Sony Exmor back illuminated CMOS sensor
- 4K HDMI/USB multiple video outputs
- 4K/1080P auto switching according to the display resolution
- SD card for the captured image and video storage
- Embedded MicroView for the control of the camera
- With strong ISP and other related processing functions
- MicroView/MicroLite software for PC
- Micaps software for MAC

Applications

- Scientific research, education (teaching, demonstration and academic exchanges)
- Digital laboratory, medical research
- Industrial visual (PCB examination, IC quality control)
- Medical treatment (pathological observation)
- Food (microbial colony observation and counting)
- Aerospace, military (high sophisticated weapons)

| Model No. | Sensor & Size(mm) | Pixel(μm) | G Sensitivity Dark Signal | FPS/Resolution | Binning | Exposure |
|---------------|--------------------------------------|-----------|--|---|---------|-------------------|
| ECO4KUHD8MPCD | Sony IMX585(C) 1/1.2"(11.14x6.26) | 2.9 x2.9 | 1028mv with 1/30s 0.13mv with 1/30s | 30@3840*2160(HDMI) 20@3840*2160(USB) | 1x1 | 0.04ms~1000 ms |

| Interface or Button | Function Description |
|---------------------|---|
| USB Mouse | Connect USB mouse for easy operation with embedded UPROView software |
| USB Video | Connect PC or other host device to realize video image transmission |
| HDMI | Comply with HDMI1.4 standard. 4K or 1080P format video output for standard monitor |
| SD | SD card, comply with SDIO3.0 standard and SD card could be inserted for video & images saving |
| ON/OFF | Power switch |
| LED | LED status indicator |
| DC12V | Power adapter connection (12V/1A) |

| Video Output Interface | Function Description |
|--|--|
| HDMI Interface | Comply with HDMI1.4 standard 30fps@4K or 30fps@1080P |
| USB Video Interface | Connecting USB Video port of PC for video transfer MJPEG format video |
| Software Environment under LAN/WLAN/USB Video Output | |
| White Balance | Auto White Balance |
| Color Technique | Super-Fine Color Engine |
| Capture/Control SDK | Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc) |
| Recording System | Still Picture or Movie |
| Operating System | Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 / 10 / 11(32 & 64 bit),OSx(Mac OS X), Linux |
| PC Requirements | CPU: Equal to Intel Core2 2.8GHz or Higher, Memory: 4GB or More, Display:19" or Larger, CD-ROM |

| Other Function | Function Description |
|---------------------------|---|
| Video Saving | Video format: 8M(3840*2160) H264/H265 encoded MP4 file Video saving frame rate:30fps |
| Image Capture | 8M (3840*2160) JPEG/TIFF image in SD card |
| Measurement Saving | Measurement information saved in different layer with image content Measurement information is saved together with image content in burn in mode |
| ISP | Exposure(Automatic / Manual Exposure) / Gain, White Balance(Manual / Automatic / ROI Mode), Sharpening, 3D Denoise, Saturation Adjustment, Contrast Adjustment, Brightness Adjustment, Gamma Adjustment, Color to Gray, 50HZ/60HZ Anti-flicker Function |
| Image Operation | Zoom In/Zoom Out, Mirror/Flip, Freeze, Cross Line, Overlay, Embedded Files Browser, Video Playback, Measurement Function |
| Embedded RTC(Optional) | To support accurate time on board |
| Restore Factory Settings | Restore camera parameters to its factory status |
| Multiple Language Support | English / Simplified Chinese / Traditional Chinese / Korean / Thailand / French / German / Japanese / Italian / Russian |

| Software Environment under LAN/WLAN/USB Video Output | |
|--|--|
| White Balance | Auto White Balance |
| Color Technique | Super-Fine Color Engine |
| Capture/Control SDK | Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc) |
| Recording System | Still Picture or Movie |
| Operating System | Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 / 10 / 11(32 & 64 bit), OSx(Mac OS X), Linux |
| PC Requirements | CPU: Equal to Intel Core2 2.8GHz or Higher, Memory: 4GB or More, Display:19" or Larger, CD-ROM |

| Operating Environment | |
|--|-----------|
| Operating Temperature (in Centidegree) | -10°~ 50° |
| Storage Temperature (in Centidegree) | -20°~ 60° |
| Operating Humidity | 30~80%RH |
| Storage Humidity | 10~60%RH |



LABLINK INSTRUMENTS

- Plot no. 337, Sector 2, HSIIDC Saha, Saha, Ambala (Haryana) India - 133104.
- Plot no 3-6-164/2, 2nd Street, Hyderguda Himayatnagar, Hyderabad (Telangana) India - 500029.

Contact us:

Email:- info@lablinkinstruments.com
www.lablinkinstruments.com, www.micaps.com

