



# MICAPS TINYCMOS8300CA

CMOS eyepiece Cameras USB 2.0



Micaps Tincmos is a budget-friendly CMOS eyepiece camera designed with a simple, compact structure. It uses a USB 2.0 connection for easy data transfer. This microscope eyepiece camera has a 23.2 mm diameter, making it a perfect fit for most standard microscopes. Despite its small size, it delivers smooth, high-frame-rate video over USB 2.0, ensuring a seamless viewing experience without lag. It comes bundled with Micaps' powerful image and video processing software, giving you advanced tools for capturing and analyzing your observations. The Tincmos is ideal for turning traditional monocular or binocular student microscopes into digital microscopes. And with optional adapters (23.2 to 30 mm or 23.2 to 30.75 mm rings), it can also upgrade stereo microscopes into fully digital systems.

### Features

- Microscope eyepiece camera with 23.2 diameter and compact size
- Easy to extend to C Mount camera with high quality lens (optional)
- High-quality camera with Aptina and Sony CMOS sensor
- High-speed USB2.0 interface and high frame rate video display keep the screen smooth without interruption
- Auto white balance and auto-exposure; Brightness, contrast, chroma, and saturation can be adjusted
- With advanced video & image processing application MICAPS MicroView
- Providing Windows/Linux/Mac OS multiple platforms SDK

### Applications

- Scientific research, education (teaching, demonstration and academic exchanges)
- Digital laboratory, medical research
- Industrial visual (PCB examination, IC quality control)
- Medical treatment (pathological observation)
- Food (microbial colony observation and counting)
- Aerospace, military (high sophisticated weapons)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
TINYCMOS8300CA	8.3M/IMX274(C) 1/2.5" (6.22x3.50)	1.62x1.62	236mV 70dB 43dB	30@3840x2160 30@1920x1080 30@1280x720 30@960x540	1x1 1x1 1x1	0.1-2000 ms

### Software Environment Under Lan/wan/usb Video Output

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto/ROI/Manual White Balance
Color Technique	Super Fine Color Engine
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc);
Recording System	Still Picture and Movie
Data Format	MJPEG
Cooling System*	Natural
Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 /10(32 & 64 bit), OSx(Mac OS X), LINUX
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher, Memory: 4GB or More, Ethernet Port: RJ45 Ethernet Port, Display:19" or Larger, CD-ROM

### Operating Environment

Operating Temperature (in Centidegree)	-10°~50°
Storage Temperature (in Centidegree)	-20°~60°
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB port

### LABLINK INSTRUMENTS

- Plot no. 337, Sector 2, HSIIDC Saha, Saha, Ambala (Haryana) India - 133104.
- Plot no 3-6-164/2, 2nd Street, Hyderguda Himayatnagar, Hyderabad (Telangana )India - 500029

### Contact us:

Email:- info@lablinkinstruments.com  
www.lablinkinstruments.com, www.micaps.com

