



MICAPS

MD1080P1560 HDMI Displayer

The MD1080P1560 is designed to perfectly complement Micaps' AIOAFM series HDMI cameras, providing a high-definition display solution that is simple, flexible, and user-friendly. It features a high-quality IPS (Super TFT) LCD panel, ensuring a wide viewing angle and excellent contrast for clear, vibrant imaging. When paired with an AIOAFM HDMI camera, the MD1080P1560 enhances overall system performance—delivering fast frame rates and accurate color reproduction, making it an ideal choice for real-time imaging applications.

Features

- True 1080P HDMI displayer
- 15.6 inch active area
- IPS LCD panel, 178 degree wide viewing angle
- HDR dynamic image enhancement
- 72% SRGB primary gamut
- 400cd/m2display brightness, high contrast ratio up to 1200:1
- Standard HDMI interface
- 4mm narrow frame design on three sides, with 90% of the screen area, great visual experience
- No delay is felt with 3ms response, and dynamic definition is optimized to keep the picture stable and clear
- Without residual shadow
- Connect computer to realize screen projection, splitting and expansion
- Integrated invisible folding support, easy viewing angle adjustment
- Easy to connect with HDMI camera

| Model | Active Area(Inch) | Video Fomat | Resolution | Contrast | Color Gamut | View Angle | Touch Function |
|-------------|-------------------|-------------|------------|----------|-------------|---------------------|----------------|
| MD1080P1560 | 15.6 | HDMI | 1080P | 1200:1 | 72% SRGB | IPS Full View(178°) | NA |

Specification

| Basic performance | |
|------------------------|--|
| MD1080P1560 | Common |
| LCD Panel | IPS LCD Screen(Super TFT) |
| Input Video Format | HDMI |
| Native Resolution | 1920 x 1080 |
| Display Type | 16:9 Ratio 15.6 Inch Active Matrix Super TFT LCD |
| Typical Contrast Ratio | 1200:1 |
| Colors | 16.7 Million |
| Viewing Angle(L/R/U/D) | IPS Full View(178°) |
| Active Display Area | 344.16mm(W) × 193.59mm(H) |
| Pixel Pitch | 0.179(W) X 0.179(H) mm |
| Refresh Rate | 60Hz |
| Brightness | 400cd/m 2 |
| Backlight | LED Backlight, 50000 hours |

| Outline Parameter | |
|-------------------------|-------------------------------------|
| Color | Black |
| Dimension | 356.1(L)*213.21(H)*11.8(T) mm |
| Weight | 750g |
| Operating Environment | |
| Operating Temperature | -0Degree~40 Degree |
| Humidity Non Condensing | Operating:10%-80%, Storage: 5%-90% |
| Synchronization Range | 148.5KHz Horizontal, 60 Hz Vertical |
| Power Supply | AC100V-240V /DC12V(3A) (Type C) |
| Power Consumption | Max 15W |



Right Side View of MD1080P Displayer and AIOAFM Series HDMI Camera's Connection



Back View of MD1080P1560 Displayer and AIOAFM Camera's Connection



AIOAFM Camera and MD1080P1560 DISPLAYER

LABLINK INSTRUMENTS

- Plot no. 337, Sector 2, HSIIDC Saha, Saha, Ambala (Haryana) India - 133104.
- Plot no 3-6-164/2, 2nd Street, Hyderguda Himayatnagar, Hyderabad (Telangana)India - 500029

Contact us:

Email:- info@lablinkinstruments.com
www.lablinkinstruments.com, www.micaps.com

