



MICAPS HPSCMOS1200CA

C-mount USB 2.0 CMOS Cameras
SONY STARVIS CMOS Sensor



The HPSCMOS1200CA camera features a top-notch SONY STARVIS CMOS sensor for capturing images, with USB2.0 serving as the data transfer interface. With hardware resolutions of 1.2MP, the camera is housed in a sturdy CNC aluminum alloy casing. It comes equipped with the MicroView application for advanced video and image processing. The camera also offers a versatile range of platform support, including Windows, Linux, macOS, and Android, along with multiple SDK options (Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc). Ideal for bright field light environments, the HPSCMOS1200CA is well-suited for microscope image capture and analysis, boasting a higher frame rate.

Features

- Standard C-Mount camera with Sony Starvis (Back illuminated) CMOS sensor
- Rolling Shutter
- CNC aluminum alloy housing
- USB2.0 interface ensuring high speed data transmission
- Ultra-Fine color engine with perfect color reproduction capability
- With advanced video & image processing application MicroView
- Windows/Linux/macOS/Android multiple platform SDK

Applications

- Digital laboratory, medical research
- Industrial visual (PCB examination, IC quality control)
- Medical treatment (pathological observation)
- Food (microbial colony observation and counting)
- Aerospace, military (high sophisticated weapons)
- Scientific research, education (teaching, demonstration and academic exchanges)

Model No.	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
HPSCMOS1200CA	1.2M/IMX224(C) 1/3"(4.80x3.60)	3.75 x3.75	2040mv with 1/30s 0.15mv with 1/30s	27@1280x960 54@640x480	1x1 2x2	0.105ms~15s

C: Color

Other Hardware Configuration

Spectral Range	380-650nm (with IR-filter), for Monochromatic Camera, AR Is Used
White Balance	ROI White Balance/ Manual Temp-Tint Adjustment
Color Rendering Technique	Super Fine Color Engine
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
ADC	8 Bit
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment

Operating Temperature	-10 °C~ 50 °C
Storage Temperature	-20 °C~ 60 °C
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port,

Software Environment

Operating System	Support Microsoft Windows XP / Vista / 7 / 8 / 10(32 & 64 bit)OS X (Mac OS X), Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory: 2GB or More
	USB port: USB2.0 High-speed Port
	Display: 17" or Larger
	CD-ROM



LABLINK INSTRUMENTS

- Plot no. 337, Sector 2, HSIIDC Saha, Saha, Ambala (Haryana) India - 133104.
- Plot no 3-6-164/2, 2nd Street, Hyderguda Himayatnagar, Hyderabad (Telangana)India - 500029

Contact us:

Email:- info@lablinkinstruments.com
www.lablinkinstruments.com, www.micaps.com

